

ELECTRIC OPERATION

The Roulett headrail may be motorised for tilt operation only, by a low voltage battery operated motor, controlled by an infrared handset. The motor is installed inside the headrail with the battery pack and infrared sensor positioned either on the headrail itself or fixed to any surface within 500mm of the motor. The handset can operate up to 3 individual groups of motors. For full motorisation, please refer to the specification sheet for the Novolux Mono Control Blinds.

FABRICS/MATERIALS

Roulett rails are manufactured from cold rolled steel 0.5mm thick, corrosion resistant, with a baked enamel surface. The rails are formed after painting the headrail into 27mm wide by 19mm deep U-shaped profile, with rolled edges at top and bottom rail, into 25mm wide by 10mm deep for the 25mm Privacy slats.

The 25mm Privacy slat is available in a range of over 130 colours including pearlised, metallic and perforated.

Ladder braid is manufactured from high density braided polyester yarn in a ladder formation. The braid is equally spaced at 18mm for 25mm slat. Lift cord is 1.4mm diameter braided polyester with a reinforced core, and the cord is secured to the bottom rail using an internal tape lock button. All textiles are fully colour co-ordinated to the slatting.

FIXING

There is a range of different types of fixing brackets made from galvanised steel and providing secure, easy and quick mounting of the blind. The brackets allow the blind to be easily removed for cleaning.

A fitting to secure the venetian blind bottom rail by means of hold-down brackets is available and is made of plastic.

MAINTENANCE

Care of the venetian slats is simple – just a light dusting, cleaning with a damp cloth or even vacuuming at a low setting, will keep them looking good.



RECOMMENDATIONS

Maximum Width	2600mm
Minimum Width	210mm
Maximum Recommended Area	4.5 sq m

DECLARATION OF QUALITY: All products detailed in this literature are manufactured exclusively in our own factory. This allows complete control over quality and also enables delivery to be tailored and guaranteed for each individual project. We are constantly striving to improve the product and reserve the right to alter specifications without notice.