

PRODUCT DESCRIPTION

Venetian blinds, with slats manufactured from aluminium alloys coated with polyester-based paint, combine high functional efficiency with strong aesthetic appeal and are available in a wide range of colours, with colour co-ordinated rails, braids and cords.

UNO STANDARD OPERATION

The attractive yet robust design of the Uno makes the system suitable for volume sales and a wide range of applications using 25mm slats. The headrail size is 25mm by 25 mm which also allows for motorization with switch or remote control.

PRESIDENT STANDARD OPERATION

Chain operation is the standard control and may be fitted either on the face or the end of the headrail at either side of the blind. The length of the chain remains the same whether the blind is raised or lowered. Crank operation is used for larger blinds; this can either be fixed or removable.

PRESIDENT MONO CONTROL OPERATION

The mono control President shares the same heavy-duty headrail as the Classic, but the use of different internal components allows it to be used for mono control. Cord operation is the standard method of control and is available fitted at either end of the headrail. Crank operation is also available and both crank and cord operation can be manufactured to suit double glazing applications.

CLASSIC AUDIO-VISUAL

This version of the Classic blind allows 70% partial blackout, particularly suitable for schools and lecture theatres. The audio-visual blind has a plastic channel 55mm wide and 50mm deep that is used as a light trap and is fixed on the sides and bottom of the window recess. The blind is also fitted with wide ladder tape to obscure light entry through cord holes.

ELECTRIC OPERATION

Electric operation for the President is also available using Somfy 240v tubular motors, and the Uno blind can be motorized using tried and tested Somfy low voltage tubular motors. Blinds can be operated individually, in groups, or with automatic sun-sensing equipment. Switching can be either wall-mounted switches or infrared handsets.

FIXING

There is a range of different types of fixing brackets made from galvanised steel and providing secure, easy and quick mounting of the blind. The brackets allow the blind to be easily removed for cleaning.

A fitting to secure the venetian blind bottom rail by means of hold-down brackets is available and is made of plastic.

MAINTENANCE

Care of the venetian slats is simple – just a light dusting, cleaning with a damp cloth or even vacuuming at a low setting, will keep them looking good.

**RECOMMENDATIONS:**

	Min Width	Max Width	Max Drop	Max Area
Uno				
Chain Operation:	250mm	2000mm	3000mm	4 sq m
Electric Operation:	600mm	3500mm	3500mm	5 sq m
President (50mm Slat)				
	400mm	4000mm	3050mm	8 sq m
Classic				
	220mm	4000mm	4000mm	10 sq m

DECLARATION OF QUALITY: All products detailed in this literature are manufactured exclusively in our own factory. This allows complete control over quality and also enables delivery to be tailored and guaranteed for each individual project. We are constantly striving to improve the product and reserve the right to alter specifications without notice.