

SLIMLINE ELECTRIC OPERATION

The slimline systems can be motorised for tilting operation only. This is done with a battery-operated motor controlled by a remote handset. The motor can be fitted either to new blinds or retro-fitted to existing ones. The long life battery operation means that there are no requirements for electrical wiring and installation is as simple as an ordinary blind. The handset can control any number of blinds, individually or in groups. A manual control is provided to draw the slats open and closed. For full motorisation of the headrail with either switch or remote control a separate system is available. Details on request.

FABRICS/MATERIALS

All the fabrics in our range have been specifically designed and manufactured for vertical blinds. Most are available in 89mm and 127mm wide louvres as standard. All fabrics used in the contract market are flame-resistant.

Another major factor in the choice of fabrics for modern buildings with large areas of glass is that of solar gain. SPC has a special, solar protective, reflective coating applied to one side of the fabric only. The application improves the fabric's solar performance significantly and also reduces glare on VDU screens.

At the other end of the scale are opaque fabrics. These have a zero light transmittance. Again refer to individual fabric specifications for exact solar and optical figures of each fabric.

Many vertical blind fabrics are also manufactured in matching roller and pleated blinds. This also includes some of the SPC fabrics. Please refer to individual fabric specifications for the exact standards.

FIXING

There is a wide selection of brackets with varying projections to suit every installation including face, top and side fixing versions. Top fix brackets are extremely neat and the snap-on fixing facilitates easy fitting and removal. There are four sizes of face-fixing brackets, two of them adjustable. The longest holds the centre of the blind 180mm from the mounting surface. Side fixing brackets are useful where it is not easy to face or top fix. Please note that drilling fixing holes in the track is not recommended, as this interferes with the smooth operation of the blind and can eventually cause permanent damage.

The louvres on a cord and chain blind can be arranged to part in the middle (split draw) or to bunch one side (one way draw). They can also be made to bunch in the centre of the blind (centre draw).

MAINTENANCE

Vertical Blinds are self-lubricating and require minimal maintenance. However, the occasional application of silicone spray lubricant ensures efficient long-term operation.

Fabric Louvres can be lightly sponged with a very mild detergent solution to clean. Aquatek is the only fabric range that is guaranteed as a truly washable material.



RECOMMENDATIONS:

Maximum Width	
Slimline:	5000mm
Maestro:	5000mm
Crank Handle:	5000mm
Electric Tilt Only:	3500mm

DECLARATION OF QUALITY: All products detailed in this literature are manufactured exclusively in our own factory. This allows complete control over quality and also enables delivery to be tailored and guaranteed for each individual project. We are constantly striving to improve the product and reserve the right to alter specifications without notice.