

CONTROLS

As standard, the tilter mechanism and cord locks are in the traditional pattern with separate raise /lower and tilt cords normally at opposite ends of the headrail. If required, the controls may be positioned at either side of the headrail. For free-hanging blinds, a tilt wand can be supplied in preference to the cord operated tilter.

FABRICS/MATERIALS

Standard blinds are supplied with co-ordinating high-density braided polyester yarn in a ladder formation, which is both functional and unobtrusive. The braid is equally spaced at 21.5mm for 25mm slat and 42mm for a 50mm slat. The lift cord is 2.3mm diameter, braided polyester with a reinforced core and all matching cords come fitted with a shaped toggle as standard. Create that unique individual look by selecting from a choice of over 25 co-ordinating woven ladder tapes. 38mm and 25mm wide ladder tape is available for 50mm slat whereas 25mm wide ladder tape is available for 25mm slats.

FIRE RETARDANT

All our Timbercraft Blinds can be flame proofed to BS476 Class I. A copy of this certification can be supplied with each order. Timber Impression blinds do not require FR treatment as the slats are inherently flame retardant.

FIXING

The fixing brackets made from galvanised steel and provide secure, easy and quick mounting of the blind. The brackets allow the blind to be removed for cleaning. A fitting to secure the venetian blind bottom rail by means of hold-down brackets is available and is made of plastic.

MAINTENANCE

Care of the venetian slats is simple- just a light dusting, cleaning with a damp cloth, or even vacuuming at a low setting will keep them looking good.

25mm PERFECT FIT

Perfect Fit is available with the 25mm Timbercraft Wood Venetian Blinds, these are fitted onto the Roulett headrail.

STACKING SIZE FOR RECESS OR FASCIA DEPTH

O/A Blind Size	Classic Rail 50 mm	Continent Rail 25mm	Classic Rail 50 mm	Continent Rail 25 mm
	Ladder Braids		Ladder Tapes	
600	115	130	140	170
900	135	170	170	220
1200	155	210	195	270
1500	175	255	220	325
1800	200	295	250	375
2100	220	340	275	430
2400	240	380	300	480
2700	265	420	330	530
3000	285	460	360	580



options are standard stringtape or laddertape



RECOMMENDATIONS

Minimum Width	220mm
Maximum Width	
Timbercraft Bamboo 25mm:	1828mm
Timbercraft Bamboo 50mm:	2438mm
Timbercraft Gloss 50mm:	2438mm
All other slats:	2743mm
Maximum Drop	3050mm
Maximum Area	4.5 sq m

DECLARATION OF QUALITY: All products detailed in this literature are manufactured exclusively in our own factory. This allows complete control over quality and also enables delivery to be tailored and guaranteed for each individual project. We are constantly striving to improve the product and reserve the right to alter specifications without notice.